


# 110011 LM\_LED\_E27 - V1



COMMISSION DELEGATED REGULATION (EU) 2019/2015  
with regard to energy labelling of light sources

EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

## Informacione të përgjithshme

|                       |               |
|-----------------------|---------------|
| Trade mark            | EGLO          |
| Numri i artikullit    | 110011        |
| Lloji                 | poq           |
| Light colour Complete | WARM WHITE    |
| Lloji i ndriqesit (1) | E27-LED-G95   |
| EAN/UPC               | 9008606227495 |

## Dimenzionet

|                     |     |
|---------------------|-----|
| Diametri (në mm/in) | 95  |
| Gjatësia (në mm/in) | 137 |

# 110011

## LM\_LED\_E27 - V1

### Informacione teknike

|                                                     |          |
|-----------------------------------------------------|----------|
| Equivalent power (W)                                | 75       |
| item-number LED-board (1)                           | 110011   |
| Lighting Technology                                 | LED      |
| Directional Light source                            | No       |
| Lamp cap (Socket)                                   | E27      |
| Mains light source                                  | Yes      |
| Connected light source                              | No       |
| Colour-tunable light source                         | No       |
| High luminance light source                         | No       |
| Dimmable (bulb, board, stripe,...)                  | No       |
| Energy consumption (kWh/1000h)                      | 8        |
| Rated useful lumen                                  | 1055     |
| Beam angle (°) - at measurement                     | 360      |
| Color temperature (K)                               | 2700     |
| Nominal wattage (W)                                 | 8        |
| Chromaticity coordinates x (1)                      | 0,4586   |
| Chromaticity coordinates y (1)                      | 0,4224   |
| Color rendering index (CRI)                         | 80       |
| Lamp survival factor @3000h                         | > = 90 % |
| Lumen maintenance factor @3000h % in decimal number | 0,93     |
| Displacement factor DF (PF)                         | 0,7      |
| Flicker Metric / Pst LM                             | 0,1      |
| Stroboscopic Effect Metric / SVM                    | 0,1      |

