


# 110152 LM\_LED\_G9 - V1



COMMISSION DELEGATED REGULATION (EU) 2019/2015  
with regard to energy labelling of light sources

EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

## General Information

|                 |               |
|-----------------|---------------|
| Trade mark      | EGLO          |
| Materijal broj  | 110152        |
| Tip             | Žarulje       |
| Boja svjetla    | WARM WHITE    |
| Tip žarulje (1) | G9-LED        |
| EAN kod         | 9008606228768 |

## Dimensions

|                             |    |
|-----------------------------|----|
| Promjer proizvoda (u mm/in) | 15 |
| Dužina proizvoda (u mm/in)  | 60 |

### Technical Information

|                                                     |          |
|-----------------------------------------------------|----------|
| Equivalent power (W)                                | 20       |
| item-number LED-board (1)                           | 110152   |
| Lighting Technology                                 | LED      |
| Directional Light source                            | No       |
| Lamp cap (Socket)                                   | G9       |
| Mains light source                                  | Yes      |
| Connected light source                              | No       |
| Colour-tunable light source                         | No       |
| High luminance light source                         | No       |
| Dimmable (bulb, board, stripe,...)                  | No       |
| Energy consumption (kWh/1000h)                      | 2        |
| Rated useful lumen                                  | 200      |
| Beam angle (°) - at measurement                     | 360      |
| Color temperature (K)                               | 3000     |
| Nominal wattage (W)                                 | 2        |
| Chromaticity coordinates x (1)                      | 0,4394   |
| Chromaticity coordinates y (1)                      | 0,4057   |
| Color rendering index (CRI)                         | 80       |
| Lamp survival factor @3000h                         | > = 90 % |
| Lumen maintenance factor @3000h % in decimal number | 0,93     |
| Flicker Metric / Pst LM                             | 0,2      |
| Stroboscopic Effect Metric / SVM                    | 0,2      |

