


# 110126 LM\_LED\_E14 - V1



COMMISSION DELEGATED REGULATION (EU) 2019/2015  
with regard to energy labelling of light sources

EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

## Основна информация

|                              |                      |
|------------------------------|----------------------|
| Trade mark                   | EGLO                 |
| Артикулен номер              | 110126               |
| Тип                          | Източник на светлина |
| Светлинен цвят общо          | WARM WHITE           |
| Тип източник на светлина (1) | E14-LED-C37          |
| EAN/UPC код                  | 9008606228539        |

# 110126

## LM\_LED\_E14 - V1

### Техническа информация

|                                                     |          |
|-----------------------------------------------------|----------|
| Equivalent power (W)                                | 40       |
| item-number LED-board (1)                           | 110126   |
| Lighting Technology                                 | LED      |
| Directional Light source                            | No       |
| Lamp cap (Socket)                                   | E14      |
| Mains light source                                  | Yes      |
| Connected light source                              | No       |
| Colour-tunable light source                         | No       |
| High luminance light source                         | No       |
| Dimmable (bulb, board, stripe,...)                  | Yes      |
| Energy consumption (kWh/1000h)                      | 6        |
| Rated useful lumen                                  | 470      |
| Beam angle (°) - at measurement                     | 360      |
| Color temperature (K)                               | 3000     |
| Nominal wattage (W)                                 | 5,5      |
| Chromaticity coordinates x (1)                      | 0,44     |
| Chromaticity coordinates y (1)                      | 0,403    |
| Color rendering index (CRI)                         | 80       |
| Lamp survival factor @3000h                         | > = 90 % |
| Lumen maintenance factor @3000h % in decimal number | 0,96     |
| Displacement factor DF (PF)                         | 0,5      |
| Flicker Metric / Pst LM                             | 0,4      |
| Stroboscopic Effect Metric / SVM                    | 0,4      |

