


# 110033 LM\_LED\_E27 - V1



COMMISSION DELEGATED REGULATION (EU) 2019/2015  
with regard to energy labelling of light sources

EGLO Leuchten GmbH, Heiligkreuz 22, 6136 Pill, AT

## Opće informacije

|                 |               |
|-----------------|---------------|
| Trade mark      | EGLO          |
| Materijal broj  | 110033        |
| Tip             | Žarulje       |
| Boja svjetla    | WARM WHITE    |
| Tip žarulje (1) | E27-LED-A60   |
| EAN kod         | 9008606227693 |

## Dimenzije

|                             |     |
|-----------------------------|-----|
| Promjer proizvoda (u mm/in) | 60  |
| Dužina proizvoda (u mm/in)  | 105 |

### Tehnički podaci

|                                                     |          |
|-----------------------------------------------------|----------|
| Equivalent power (W)                                | 60       |
| item-number LED-board (1)                           | 110033   |
| Lighting Technology                                 | LED      |
| Directional Light source                            | No       |
| Lamp cap (Socket)                                   | E27      |
| Mains light source                                  | Yes      |
| Connected light source                              | No       |
| Colour-tunable light source                         | No       |
| High luminance light source                         | No       |
| Dimmable (bulb, board, stripe,...)                  | No       |
| Energy consumption (kWh/1000h)                      | 7        |
| Rated useful lumen                                  | 806      |
| Beam angle (°) - at measurement                     | 360      |
| Color temperature (K)                               | 2700     |
| Nominal wattage (W)                                 | 7        |
| Chromaticity coordinates x (1)                      | 0,4606   |
| Chromaticity coordinates y (1)                      | 0,4229   |
| Color rendering index (CRI)                         | 80       |
| Lamp survival factor @3000h                         | > = 90 % |
| Lumen maintenance factor @3000h % in decimal number | 0,93     |
| Displacement factor DF (PF)                         | 0,71     |
| Flicker Metric / Pst LM                             | 0,1      |
| Stroboscopic Effect Metric / SVM                    | 0,1      |

