



Informazioni generali

| | |
|---------------------------------|--------------------------|
| Codice prodotto | 901014 |
| Modello | Plafoniera |
| Segmento prodotto | Indoor |
| Tema | altro / non attribuibile |
| Classe di efficienza energetica | F |

Dimensioni

| | |
|------------------------------|-----|
| Altezza articolo (in mm/in) | 28 |
| Diametro articolo (in mm/in) | 285 |
| Peso netto (in kg) | 0,7 |

Materiale e colore

| | |
|---------------------|---------------|
| Materiale struttura | acciaio |
| Colore struttura | nero |
| Materiale diffusore | policarbonato |
| Colore diffusore | bianco |

Funzioni

| | |
|------------------------------------|---------|
| Tipo di interruttore | Sensore |
| Angolazione sensore (in °) | 160 |
| Tempo di accensione max. (in sec.) | 20 |
| Distanza (in metri) | 2,5 |
| Batteria | No |

Informazioni tecniche

| | |
|----------------------------------|------------------|
| Grado di protezione | IP20 |
| Classe di protezione | 2 |
| Tensione di rete | 220-240V,50/60Hz |
| Dimmerabile | No |
| Watt 1 | 20,5 |
| Max.Watt Incr.Transformer/Driver | 21W |

Sorgente luminosa 1

| | |
|--|--|
| Numero di presa lampada / sorgente luminosa 1 | 1 |
| Tipo di presa 1 | LED |
| Tipo illuminante 1 | LED |
| Illuminante 1 | Incluso |
| Lumen ogni presa lampada / sorgente luminosa 1 | 2400 |
| Kelvin 1 | 3000 |
| Colore chiaro 1 | BIANCO CALDO |
| Classe di efficienza energetica | F |
| Dimmerabile | No |
| Informazioni su sostituzioni | LED + driver sostituibili da un elettricista |

| | | | | | | | |
|--|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| 1 x 20,5 W | 1 x 2400 lm | | | | INCL. | SURFACE | |

THE FUNCTIONAL GUARANTEE ONLY APPLIES TO THE USE OF THE PRODUCTS IN THE PRIVATE SECTOR AND NOT TO PRODUCTS THAT ARE USED COMMERCIALY (E.G. IN RESTAURANTS, HOTELS, RESORTS), ON A COMMUNAL LEVEL OR IN GENERAL AREAS OF MULTI-PARTY HOUSES.

L'azienda produttrice si riserva il diritto di apportare eventuali modifiche tecniche.

2/2



Contact | Support
eglo.com/en/eglo-worldwide